



Acoustic Treatment Pack



STANDARD COLOUR

WOODEN FINISHINGS

SLIMBASS®

Tuned Absorption

Music rooms, studios, practice rooms, etc, require an efficient surface to absorb low frequencies.

The SLIMBASS® absorbent panel is an ATP® proposal for low-frequency absorption.

It is made of high quality cell controlled, self-extinguishable M1 fire-retardant acoustic foam and epoxy PVC. It has inside it a closed resonance box tuned to 160 Hz, which has an exclusive membrane.

SLIMBASS® panels present a slim and elegant design suitable to fit in the room's corners to solve most acoustic anomalies in low and mid-low frequencies.

Features:


- NRC average: 0.75 / m2 [$>250\text{Hz}; <1\text{KHz}$].
- Self-extinguishable M1 fire-retardant acoustic foam.
- Installation: glues included.
- In stock for immediate delivery.
- Very easy to install.
- Other colours available upon consultation.



Package Data:

	SLB120			
	H	W	D	Kg
4 units/box	124 cm	64 cm	30 cm	8.2

Technical Drawing:



Values:

															Absorption Coefficient										
Hz	50	63	80	100	125	160	200	250	315	400	500	630	800	1k	1.25k	1.6k	2k	2.5k	3.15k	4k	5k	6.3k	8k	10k	NRC [$>100\text{Hz}; <250\text{Hz}$]
α_s	0.10	0.17	0.32	0.42	0.72	0.89	0.86	0.88	0.86	0.73	0.67	0.58	0.50	0.45	0.42	0.43	0.44	0.41	0.39	0.40	0.38	0.41	0.41	0.38	0.75

— Values in accordance with the standards: EN 20654, ASTM C423 and EN 11654. Non Standard values.

Model Sizes:

	H	W	D	Kg
SLB120	120 cm	30 cm	30 cm	1.4

Graphic:

